

DATI TECNICI / DONNÉES TECHNIQUES

	X30			
	S + AS	CP	CP + AS	CS
Tasti di selezione dosati Touches de sélection dosées	24 12 x 2 8 x 3 4 x 6	24 12 x 2 8 x 3 4 x 6	24 1	12 x 2 8 x 3 4 x 6
Selezioni acqua calda / Touches de sélection eau chaude	2	2	2	2
Erogatore acqua calda / Tuyau eau chaude	1	1	1	1
Acqua aggiunta / Rajout d'eau	✓	✓	✓	✓
Lancia vapore / Tuyau vapeur	-	1	-	1
Auto Steam Cold Touch	1	-	1	-
MilkPS	-	✓	✓	✓
Snowmilk	-	✓	✓	✓
Smart Boiler	✓	✓	✓	✓
PGS	✓	✓	✓	✓
Caldaia / Chaudière	2	2	2	2
Capacità caldaia / Capacité chaudière	0,7 L	0,7 L	0,7 L	0,7 L
Capacità caldaia acqua calda e vapore / Capacité chaudière eau chaude et vapeur	1,25 L	1,25 L	1,25 L	1,25 L
Macinadosatori / Moulins-doseurs	2	2	2	2
Capacità tramogge / Capacité trémies	2 x 1,2 Kg	2 x 1,2 Kg	2x 1,2 Kg	1 x 1,2 + 1 x 1,0 Kg
Tramoggia solubili / Trémie poudres solubles	-	-	-	1
Capacità tramoggia solubili / Capacité trémie poudres solubles	-	-	-	1,0 Kg
Mixer solubili / Mélangeur poudres solubles	-	-	-	✓
Wi-Fi bidirezionale / Wi-Fi bidirectionnelle	✓	✓	✓	✓
USB	✓	✓	✓	✓

X30			
DIMENSIONI / DIMENSIONS			
Dimensioni L x P x H (mm) Dimensions L x P x H (mm)	370 x 620 x 762		
Peso (kg) / Poids (kg)	79		
	220-240V 50Hz 220V 60Hz	(w)	4800 - 5700 4800
Potenza massima a Absorption à	380-415V3N 50Hz 380V3N 60Hz	(w)	4800 - 5700 4800
	220-240V 50Hz 220V 60Hz	@16 AMP (w)	3300 - 3800 3400

OPTIONAL

	S + AS	CP	CP + AS	CS
Becco motorizzato / Bec motorisé	✓	✓	✓	✓
Microfiltro / Microfiltre	✓	✓	✓	✓
Scarico diretto / Déchargement direct	✓	✓	✓	✓

