














Dati Tecnici - Specifications

											
	cond	comp. W	ABS. W	Fuse	Kwh/100Kg	l / h	kg	Lbs	kg	Lbs	Ton CO2 equiv.
M502 A		6274	2550	20	13.47	20.2	98	216	116	256	6,28
M502 W		-	-	-	-	-	-	-	-	-	-



Produzione Ghiaccio - Ice Production


Raffreddamento ad aria - Air Cooled Unit

Temp. aria Air Temp.	Temp. acqua / Water Temp.			
	32°	21°	15°	10°
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	415	440	453	465
50°	915	970	999	1025
21°	385	410	425	431
70°	849	904	936	950
32°	307	341	353	364
90°	677	752	778	802
38°	276	307	316	326
100°	608	677	696	719


Raffreddamento ad acqua - Water Cooled Unit

Temp. aria Air Temp.	Temp. acqua / Water Temp.			
	32°	21°	15°	10°
°C	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°				
50°				
21°				
70°				
32°				
90°				
38°				
100°				


Vista frontale
Front view




Vista laterale
Lateral view



Vista superiore
Top view




AIR COOLED 




Back View

WATER COOLED 



Back View



A Water drain Ø20 mm

B Potable water inlet 3/4 GAS

C Electrical cable supply

D Water cooled inlet 3/4 GAS

E Water cooled outlet 3/4 GAS



PANNELLO DI CONTROLLO - CONTROL PANEL

	Alimentazione Powered
	In Funzionamento Operating
	Deposito Pieno/Lavaggio Storage Full / Washing
	Allarme Alarm
	Allarme Alta Pressione High Pressure Alarm
	Pulsante Reset/Lavaggio Button Reset/Washing


DIMENSIONI - DIMENSIONS

LxPxH(mm): 760 x 620 x 725
WxDxH(in):2915/16"x247/16"x289/16"

DEPOSITO - SLOPE BIN

D205 - D255 - D305 (KM305)
D405 KFM404) - D505 (KFM505)


TIPO GHIACCIO - ICE TYPE



HALF-LARGE
10 x 29 x 24 - 6 gr

555


PZ. / CICLO PCS / CYCLE



DICE
22 x 22 x 24 - 10 gr

342

PZ. / CICLO PCS / CYCLE



LARGE
29 x 29 x 24 - 17 gr

210

PZ. / CICLO PCS / CYCLE

CONDIZIONI USO-OPERATING REQUIREMENTS



220-240V / 1 / 50HZ R452A GWP=3922

MIN MAX

10°C (50°F) 40°C (104°F)

5°C (41°F) 35°C (95°F)

- 10% + 10%

1 BAR (14 PSI) 5 BAR (70 PSI)

Calore espulso - Rejected Heat **6581 W**

Volume aria - Air Volume **1180 m³/h**